

864 4005 – 864 4050 HDBaseT Installation Cable Pro. standard length

Functions	HDBaseT transmission LAN up to 10 Gbit / 1500 MHz CAT7
Cable design	PIMF 4 x 2 x 0,56 / S/FTP AWG 23/1 Outer diameter 7 mm Fire retardant IEC 60332-1 Halogen free IEC 60754-2 Smoke density IEC 61034
Colour	orange
Transmission length	HDBaseT up to 100 m with TLS HDBaseT devices
Packaging / plugs	Cable length from 5 m to 50 m, step 5 m Custom design / every length possible RJ45 professional plugs / cast metal housing In-field-assembly / US-CAT.6A iso B
Weight	50g /m
Temperature	-20° C to 60° C static

864 4005 – 864 4050 HDBaseT Installation Cable Pro. standard length

Cable length

864 4005	HDBaseT Cable Pro. 5 m AWG23/1
864 4010	HDBaseT Cable Pro.10 m AWG23/1
864 4015	HDBaseT Cable Pro.15 m AWG23/1
864 4020	HDBaseT Cable Pro. 20 m AWG23/1
864 4025	HDBaseT Cable Pro. 25 m AWG23/1
864 4030	HDBaseT Cable Pro. 30 m AWG23/1
864 4035	HDBaseT Cable Pro. 35 m AWG23/1
864 4050	HDBaseT Cable Pro. 40 m AWG23/1

8635584	HDBaseT Cable Pro. Bulk AWG23/1
---------	---------------------------------

All cables are manufactured manually and comply to the technical specifications of HDBaseT.

We manufacture every cable length custom-made according to the specifications of HDBaseT:

836 7714	HDBaseT Cable Pro. Basic Unit 1 m AWG23/1
836 5584	HDBaseT Cable Pro. Bulk AWG23/1