

## 864 0250 QuickControl 4.0 IP

Function	Controlling of electronic devices with LAN-, RS232., IR- and open contact interfaces
Communication interface	1 x IP      bidirectional 2 x RS232 bidirektional 1 x IR      unidirectional (5/10 Volt) 2 x open contact
Connector	1 x RJ 45 socket 2 x PTR 3 pol plug 1 x PTR 2 pol plug 2 x PTR 2 pol plug
Data rate	10/100 BaseT 300-56000 baud 30 – 300kHz 24 Volt/1Ampere
Controlling QuickControl 4.0	8 x buttons backlighted 2 colours, off / red / green Describable lables for all buttons
Operating voltage	110 / 240 V, 50/60 Hz /12/24V 3A PoE 802.3af, class 3
Temperature	0 bis 45 Grad
Weight	0,150 kg

Version 1

## 864 0250 QuickControl 4.0 IP

Size	85 mm x 85 mm x 2,5 mm/Fase
Mounting	M4 SKS Lochabstand 1 x 65 mm
Depth	35 mm
Depth with connectors	50 mm
In-wall socket	2 gang

### Version 2

Size	145 mm x 85 mm x 2,5 mm Fase
Mounting	M4 SKS Lochabstand 2 x 65 mm 1 x 70 mm
Depth	35 mm
Depth with connectors	50 mm
IN-wall socket	2 gang
Colour	Aluminium anodized / brushed