

860 260 - 860 290 i3S Wireless presentation tool

Common description with basic function

The TLS i3S presentation tool is a HDMI based presentation-system, which transmits content from every HDMI source to every HDMI-based reproducing unit, using the frequency band of 5GHz.

Videos will be transmitted lippsync and without any latency, the resolution of the content is up to Full HD.

The components of i3S, sending unit and receiving unit, will be paired in some seconds by pressing 2 buttons. Daily business needs just the press of one button on the transmitter to send the content to the screen. Up to 250 transmitters can work in one system. There is no need to install software. Once paired, the i3S system is able to work with all sources and sinks with HDMI connectors. No need of a new configuration if the system moves to another room.

The TLS i3S presentation tool is a wireless system for the professional usage, it works without any software or application.

Usage and connectors

The TLS i3S presentation tool is HDMI based presentation tool, which is working in the WLAN frequency range of 5GHz and transmits content from all common AV sources to a reproducing unit. The receiving unit acts as an Accesspoint for up to 250 transmitters.

With the simple press on the Show-Me button, the content from the source will be displayed on the projector, display or TV without any latency. Devices without HDMI connectors can be connected with appropriate adapters to the i3S presentation system.

The i3S transmitter has an integrated accu with a normal operating duration of 5-6 hours. The Receiver can be powered with a standard mini USB connector or with an USB power supply. If the accu of the transmitter is discharged, operation is guaranteed with the usage of an USB power supply.

The system is able to work in a distance up to 30m indoor and because of the usage of the HDMI connector it works without any loss or latency.

Depending on the technology of the TLS i3S presentation tool it is a practical and cost effective system to transmit AV data over RF technology.

860 260 - 860 290 i3S Wireless presentation tool

Installation and application

The i3S can be installed behind every display or projector with a HDMI connector because of its modern and compact technology. The power supply can be done with the included wall power supply or with an appropriate USB port of the reproducing unit.

The i3S transmitter is directly connected to the source or with 10 cm adapting cable. The transmitter displays activity with a blue lighted ring. If the LED has a red colour, the transmitter must be recharged.

If you plug the receiver to the reproducing unit, first you will see the start screen. Then you have to press the button and the content will be displayed on the screen.

The system is ready

Common

The TLS i3S presentation tool is constructed and equipped with electronic components of newest technological standard and complies to the European regulations for fire, smoke and environment protection. The device guarantees excellent transmission of HDMI signals with all data for brilliant quality. Because of low latency you will work in a professional mode. The build-in connectors guarantee a secure and easy cabling and a long-lasting usage. The device is developed for all kinds of AV-systems and can work in every conference- meeting- and training-room with all kinds of sources and reproducers.