

875 715 HDBaseT Transmitter MF100 VGA/HDMI

Functions	<p>Transmission of VGA, Audio, HDMI; RS232; and IR up to 100 m with a CAT cable</p> <p>EDID pass through for VGA and HDMI</p> <p>Audio embedder for analog audio</p> <p>Automatic input detection for VGA and HDMI</p> <p>Manual and RS232 controlled switching of VGA and HDMI</p>
Video / resolution	<p>HDMI 1.4, Full HD/4K*2K / 3D</p> <p>4K@30Hz (4:4:4)</p> <p>4K@60Hz (4:2:0)</p> <p>1080p@60Hz</p> <p>VGA up to 1920 x 1080@60Hz</p> <p>HDCP compliant</p>
Length of transmission	HDBaseT up to 100 m with TLS HDBaseT cables
Inputs TX	<p>1 x HDMI socket / 1 x VGA socket, 1 x Audio jack 3,5 / 1 x RS232 9pin HD socket / 2 x 3,5 jack socket (IR) /Input select button</p>
Outputs TX	1 x RJ45 socket / 1 x screwed connection M3
Audio	<p>Auto Audio Video Sync lip-sync</p> <p>DTS – HD Master Audio</p> <p>Dolby True HD</p> <p>ARC Audio Return Channel</p>
Input	<p>HDMI socket</p> <p>VGA socket</p>
Output	HDBaseT OUT RJ45 socket
EDID- Data	EDID data pass through

875 715 HDBaseT Transmitter MF100 VGA/HDMI

RS232, IR	Bidirectional controlling of the reproducing devices Controlling of switching between VGA and HDMI
Operating voltage	110 / 240 V, 50/60 Hz / 2A Power over HDBaseT
Power over HDBaseT	12V 2A 24 W
Temperature	Up to 50° C
Size	125mm x 119mm x43mm / Aluminium – enclosure 1U; 19" rack
weight	1 x 0,2 kg