

## 875 222 HDMI 4K Switch / Audio 4/1 MHL

Functions	Switching from 4 different HDMI inputs (TMDS) to one output, transmission of all signals incl. audio and EDID Input no.4 supports MHL standard and can work with all compatible MHL smartphones The build-in audio-deembedder extracts the audio signal from the HDMI to digital SPDIF 5.1 or analog audio 7.1
Video / resolution	HDMI 1.4, Full HD/4K*2K / 3D 4K@30Hz (4:4:4) 4K@60Hz (4:2:0) 1080p@60Hz HDCP compliant
Length of transmission	25m input (with TLS HDMI cable) 25m output (with TLS HDMI cable)
Input	4 x HDMI socket
Output	1 x HDMI socket
Audio	Dolby surround 7.1 Auto Audio Video Sync lip-sync DTS – HD Master Audio Dolby True H According to HDMI 1.4 specification
Input	4 x HDMI socket
Output	1 x HDMI socket 1 x Cinch SPDIF 1 x Toslink SPDIF 4 x 3,5 audio jack for analog audio 7.1

## 875 222 HDMI 4K Switch / Audio 4/1 MHL

	4x Mini Jack - 7.1 analog audio output
EDID	EDID pass through
Controlling	Button; IR remote control Automatic signal detection
Operation LED	4 x LED HDMI input (green) 1 x LED HDMI output (white)
Operation voltage	110 / 240 V, 50/60 Hz / 5 VDC/ 1A
Operation temperature	Up to 40°C
Size	185,0 mm x 65,0 mm x 42,0 mm / Aluminium – enclosure Ready for 1U 19" Rack
Weight	0,3 kg