

8663040 QuickScout 4.0 MF

| | |
|---------------------------|--|
| Function | Modular presenter for VGA/Audio; HDMI und DisplayPort signals, controlling of connected, common media devices, audio deembedder, audio embedder integrated USB charging unit |
| Video Format / Resolution | HDMI 2.0, Full HD/4K*2K / 3D 4K@30Hz (4:4:4) 4K@60Hz (4:2:0) 1080p@60Hz HDCP 2.2 VGA up to 1920x1200@60Hz |
| Length of transmission | HDBaseT up to 100 m with TLS HDBaseT cable |
| Inputs | 1 x HDMI socket / 1 x VGA 15 pin HD socket; 1x 3,5 jack (Audio) / 1 x DisplayPort socket / 2 x RJ 45 socket / 1 x terminal 3 pin / 1 x terminal 4 pin / 1 x terminal 2 pin |
| Outputs | 1 x HDMI socket / 1 x 3,5 jack (Audio) / 2 x RJ 45 socket / 1 x USB socket / 1 x terminal 3 pin / 1 x 4 terminal e pin |
| Audioformat | Auto Audio Video Sync lip-sync DTS – HD Master Audio Dolby True HDI |
| Input | Embedded HDMI socket, Embedded DisplayPort socket 1x 3,5 jack socket, analog VGA Audio |
| Output | Embedded HDMI socket, 1 x 3,5 jack socket, deembedded Audio |
| EDID | EDID Management, software controlled or rotary switch |

8663040 QuickScout 4.0 MF

| | |
|----------------------------|---|
| Controlling QuickScout 4.0 | Select-Toggle-Button; opt. external buttons, Auto-signal-detection, Media controller IP-based (display units with RS232 und CEC) |
| Output RS232 | 1 x terminal 3 pin plug |
| Betriebsspannung | 110 / 240 V, 50/60 Hz /12V 3A |
| Arbeitstemperatur | 0 bis 45 Grad |
| Maße / Gewicht | 230mm x 125mm x 43mm Aluminium – Gehäuse 1U; 19" Rack |
| Gewicht | 0,8 kg |