

875240 HDBaseT/HDMI Splitter 1/4

Functions	Distribution amplifier for splitting 1 input HDMI to 4 outputs HDBaseT and 1 output HDMI. Integrated audio deembedder extracts to analog and digital audio. Cascadable up to 6 times with HDMI output EDID pass through, EDID management PoH available for RX
Video format / resolution	HDMI 1.4, Full HD/4K*2K / 3D 4K@30Hz (4:4:4) 4K@60Hz (4:2:0) 1080p@60Hz HDCP compliant
Transmission length	HDBaseT up to 70 m with TLS HDBaseT cable
Inputs	1 x HDMI socket
Outputs	4 x RJ45 socket / 1 x HDMI socket
Audio format	Unbalanced Audio DTS – HD Master Audio Dolby True HD
Input	
Output	1 x 3,5 jack L/R / 1 x RCA SPDIF
Input	1 x 3,5 jack IR
Output	1 x 3,5 jack IR
Video functions	Splitting of 1 HDMI input signal to 4 HDBaseT outputs and 1 HDMI output Cascadable up to 6 times with HDMI output

875240 HDBaseT/HDMI Splitter 1/4

Audio functions	Deembedder
Operating voltage / temperature	110 / 240 V, 50/60 Hz / 1,2 A 12 V / 5 A Power over HDBaseT 0 to 40° C
Size weight	262 mm x 145 mm x22 mm w/o feet 0,9 kg Metal housing ½ U; 19" rack